







A Rated Wall Hook Included

2.5 Gal





The Shield WATER FX extinguisher provides effective and economical protection for common combustible fires. The extinguisher uses ordinary water as its extinguishing agent and can be pressurized with regular air making recharging the extinguisher simple and economical. It is shipped empty for filling and pressurizing on site.

## **KEY FEATURES**

- Anodized metal valve assembly for superior strength and corrosion resistance.
- Industrial grade steel cylinder with polyester powder coating designed to withstand harsh environments & rough usage.
- Wall mount hardware included.
- Retention cord keeps pull pin attached to unit at all times.

PRODUCT SPECIFICATION			
UL Rated	<b>Part #</b> 50000R	<b>A</b> gent	<b>Cylinder</b>
2A		A	Steel
<b>Valve</b>	Case Qty	Unit Weight	<b>Unit Size</b>
Metal	2	8.3*	24 x 7.5 x 7.5
Unit Carton Size	<b>Case Size</b> 24.75 x 15 x 7.75	<b>UPC</b>	<b>Discharge Time</b>
24.5 x 9 x 7		850148002448	50 secs
USCG Approved	<b>DOT Compliance</b>	Mounting Hardware	<b>Warranty</b>
Yes	Yes	Wall Mount	6 year

\*Shipped empty

Shield Fire Protection
PO Box 428 • Kings Mountain, NC 28086

www.shieldprotects.com info@shieldprotects.com







SP-WATEREX/3/16/250